

simple. reliable. affordable.





Bluetooth

P25 Mobile Printer

Product features:

- · For anywhere, anytime portable receipt and label printing
- Supports Bluetooth®, USB or Serial connectivity
- Weighs under 10 ounces (270g) for easy portability
- · Fast, reliable, durable and lightweight design
- Prints 200 barcodes, receipts or coupons per charge
- Detachable battery and mounting accessories available
- Works with smartphones, PDAs, laptops and netbooks

Mobile sales and service



Blue Bamboo's Bluetooth® P25 printer provides mobile merchants,

application developers and VARs

with flexible options to configure payment solutions.

Applications:

- · Receipt Printing: Utility Meter, Prescriptions, POS, Claim checks
- Ticketing: Parking, Events, Lottery, Coupon, Voucher
- · Reporting: Test, ODB-II Reader, Pedometer, Navigation
- · Label: Shipping, Barcode

Transportation and livery

LIGHTWEIGHT AND PORTABLE

Designed for many types of printing applications, the lightweight and portable P25 provides reliable, low-cost printing in mobile and wireless environments.

RELIABLE PRINTING OPERATION

Manufactured for mobility and POS receipt printing, the P25 is built for demanding applications where reliability and performance are a priority.

✓ Food delivery and hospitality

ERGONOMIC LIGHTWEIGHT DESIGN

The P25 mobile printer is the smallest foot print Bluetooth printer in the market with a weight of under 10 ounces.

FLEXIBLE APPLICATION INTERFACE


The robust P25 supports mobile application printing over Bluetooth®, USB or serial connections, maximizing return on investment.

Works with: *















For more information, please contact

www.bluebamboo.com

* This model does not support Apple. Blue Bamboo's P25i and P25-Mi Printers do. Phone models are validated and announced by local solution partners. Solution providers build and validate the PA-DSS applications on JAVA, Android, Windows et al platforms.



P25 technical specifications

Available Bluetooth Printers

- P25 with USB
- P25 with Serial

Communication Interface Bluetooth® Class 2, up to 32 feet (10 meter) Version 2.0 + EDR SPP (Serial Port Profile) required by host device, USB 2.0 or Serial port (RS-232)

Indicator Tricolor LED for Power, Bluetooth®, Error Message

Keypad Power, Feed and Mode buttons

Print Method Direct thermal
Print Width 48mm (1.89")

Feed Speed 50 mm/sec (2.0" /sec)
Print Speed 50 mm/sec (2.0" /sec)

Paper Size 58 mm (2.3") width, 40 mm (1.6") roll diameter, 11mm (0.43") inner diameter

Print Resolution 203 dpi horizontal & vertical

Graphic Mode 384 dots wide (max.), length unlimited

Character Sets Latin alphabet: 12 x 24, 16 x 32 (Lucide font)

Chinese characters: 24 x 24, 32 x 32 Scalable up to 8 times original size

Bar Code UPC-A, UPC-E, EAN-8, EAN-13, PDF417

Tear Bar Embedded in printer mechanism

Mount Rubber pads for desk mount

Two threaded inserts for hard mount. Optional mounting solutions available.

Regulatory Approvals FCC, CE

Drop Specification 1 m (3.3') with soft skin case

Battery/Power 7.4V 1400mAH replaceable Lithium-ion battery, self discharge rate <10% week,

AC charging adapter 100-240VAC, 50/60 Hz

Dimensions(W x D x H) 75 x 96 x 46 mm (3.0 x 3.8 x 1.8")

Weight 270g/9.5oz/0.60 lbs (paper and battery included)

Software/ Development Developer guide includes reference code for Java, Windows Mobile, and WinCE OS

environments.

Environment Operating temperature: -5 ~ 50°C (+23 ~ 122°F)

Operating humidity: 20 \sim 85% RH Storage temperature: -20 \sim 60°C (-4 \sim 140°F) Storage humidity: 5 \sim 90% RH

Expected Life Print Head: 50 km (31 miles), 400 million dot lines @ 12.5% print ratio

Battery: single charge: 20 m (66 ft), 12.5% print ratio, 500 charge cycles Clamshell: 5,000

times open/close

Included Accessories Power Adapter (100~240 VAC, 50/60 Hz)

Cable (USB or Serial)
Paper Roll (15 m in length)
Rugged Soft Skin Case
Hip Mount Belt Buckle

Optional Accessories Spare Battery

Car Charger Carrying Case





RUGGED SOFT SKIN CASE (included)



HIP MOUNT BELT BUCKLE (included)





All features and specifications are subject to change without notice. All trademarks mentioned are registered by their respective owners. Contact Blue Bamboo sales for more details.

Also see Blue Bamboo P25-M which includes magnetic-stripe reader

Blue Bamboo Corporate Offices 6 Floor, Huishan Technology Park, 3333 Changning Road, Shanghai China 200336 Tel: +86 21 5219 0333 Fax: +86 21 5219 0603 USA Office Tel: 1-888-372-9266

