

Specifications	SLP-T400 Series	
Printing Method	Thermal Transfer or Direct Thermal Printing	
Print Speed	Max. 150 mm/sec (6 Inches/sec)	
Resolution	203 dpi (8 dot/mm)	
Paper	Types: Gap, Notch, Black Mark, Continuous, Fan-Fold	
	Width: 25~116 mm	
	Core: 25.4~38.1 mm	
	OD: Internal ? 130 mm, External ?220 mm	
Ribbon	Type: Wax, Wax/Resin, Resin (Outside Type)	
	Width: 33~110 mm	
	Length: Max. 300 m	
	Core ID: 12.5, 25.4 mm	
Character Set	Alpha Numeric Character: 96	
	Extended Character: 128 x 23 Pages	
	International Character: 22	
	Resident Bitmap Fonts:10	
Graphic	PCX & BMP	
Bar-code type	1D Codes:EAN-8, EAN-13, UPC-A/E, ITF, Code 39, Code 128, Code 93, Interleave 2 of 5, Coda Bar 2D Codes: QR Code, Maxicode, Datamatrix & PDF417	
Emulation	SLCS, EPLII, ZPLII, DPL & CPL	
Sensor	Transmissive Sensor, Reflective Sensor (position Adjustable), Ribbon End, Head Open Sensor	
Receive Buffer Size	256 Kbyte	
NV Image	64 Kbyte	
Interface	Serial	RS-232C
	Unidirectional Parallel	IEEE 1284
	USB	
	Ethernet	Optional
Power	24 DCV, 3.75A, External power supply	
External Dimensions (WxDxH)	214 x 310 x 200 mm	
Weight	Approx. 5.7 Kg	
Warranty	Printer Unit	12 Months
	Head	6 Months
	Auto Cutter Option	6 Months
Safety Standards	UL, C-UL, FCC Class A, TUV-GS, CE Marking	