

TTP-268M . TTP-366M

INDUSTRIAL THERMAL TRANSFER BAR CODE PRINTER

SPECIFICATIONS

Printer model	TTP-268M	TTP-366M
Resolution	203 DPI	300 DPI
Printing method	Thermal Transfer and/or Direct Thermal	
Max. print speed	Up to 8 ips	Up to 6 ips
Max. print width	168 mm (6.61")	168 mm (6.61")
Max. print length	5,080 mm (200")	2,540 mm (100")
Enclosure	Die-cast aluminum frame. Metal cover with large clear media view window	
Physical dimension	355 mm (W) x 337 mm (H) x 510 mm (D) or 13.98" (W) x 13.27" (H) x 20.08" (D)	
Weight	23 kg	
Label roll capacity	208.3 mm (8.2") OD	
Ribbon	450 meter long, max. OD 81mm, 1" core (Ink coated outside/inside)	
Ribbon width	50.8 mm ~ 178 mm (2.0" ~ 7")	
Processor	32-bit RISC CPU	
Memory	8 MB Flash memory 32 MB SDRAM - SD Flash memory card slot for Flash memory expansion	
Interface	- RS-232C (2400 - 115200 bps) - Centronics (SPP mode) - USB 2.0 (full speed) - PS/2 keyboard interface - Internal Ethernet print server (10/100 Mbps)	
Power	Internal switching power supply - Input: 90-230VAC, 47~63Hz - Output: 24V, 14.58A, 350W	
LCD display	Graphic type, 128 x 64 pixel, with back light	
Operation switch, button	1 power switch, 6 operation buttons	
Sensors	- Transmissive gap sensor (position adjustable from 2" ~ 4") - Reflective black mark sensor position full web adjustable - Transmissive ribbon end sensor	
Real time clock	Standard	
Internal fonts	8 alpha-numeric bitmap fonts - Monotype Imaging® true type font engine with one CG Triumvirate Bold Condensed scalable font	
Bar code	1D bar code Code 39, Code 93, Code128UCC, Code 128 subsets A,B,C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11 2D bar code PDF-417, Maxicode, DataMatrix, QR code, Aztec	
Font and barcode rotation	0, 90, 180, 270 degree	
Command set	TSPL-EZ™	
Media type	Continuous, die-cut, fan-fold, tag, notched, black mark (Outside wound)	
Media width	50.8 ~ 172.7mm (2" ~ 6.8")	
Media thickness	0.06 ~ 0.254 mm (2.36 ~ 10 mil)	
Media core diameter	76.2 mm (3")	
Label length	10 ~ 5,080 mm (0.39" ~ 200") 25.4 ~ 152.4 mm (1" ~ 6") for peeler mode 25.4 ~ 5,080 mm (1" ~ 200") for cutter mode	
Environment condition	Operation: 5 ~ 40°C, 20 ~ 85% non-condensing Storage: -40 ~ 60°C, 10 ~ 90% non-condensing	
Safety regulation	FCC Class A, CE Class A, CCC	
Environmental concern	Comply with RoHS, WEEE	
Accessories	- BarTender UltraLite labeling software CD disk - Quick start guide - USB cable - Power cord - Ribbon take-up paper core	
Limited warranty	Print head: 1 million inches (25 km) or 12 months which comes first Printer: 2 years Platen: 50 km	
Factory options	Applicator I/O interface	
Dealer options	- Peel-off kit (include internal rewind & peel off module) - Heavy Duty Cutter module Max. paper width: 178mm (7") Paper thickness: Max 0.25mm (max. paper weight 250 g/m²), 1,000,000 cuts	
User options	- Bluetooth module (serial interface) - KP-200 Plus keyboard display unit - KU-007 Plus programmable smart keyboard - HCS-200 long rang CCD scanner	