TOGETHER COMMERCE

TCxWave Technical Requirements

Preloads	Windows 7, POSReady 7, POSReady 2009 (*only 32-bit is available preloaded)
Supported Operating Systems	Windows 7(64-bit and 32-bit), POSReady 7, POSReady 2009, 4690*(support target year end 2013 Version 6 Enhanced), Windows 8 *(support targeted year end 2013)
Processor and FSB Speed	Intel Celeron 847e (2M Cache, 1.10 GHz)
Chipset	Intel HM65PCH
BIOS	AMI
Memory*,†	DDR3 1066 MHz 2GB Standard 8GB Max
Video	Intel Integrated Graphics Device (DisplayPort output)
Touch	Projected Capacitive Touch Technology 5 point multi-touch*(Hardware Support Statement)
Screen	LCD 18.5 in. 16:9 LED back-lit LCD
Audio	Internal PC Speaker
Storage	Solid State Drive 64 GB
sLAN†	10/100 MB
Expansion	N/A
I/O Ports and connections Dockable Base	(1) 24 V Powered USB 2.0, (3) 12 V Powered USB 2.0, (3) PC USB 2.0, (1) 10/100/1000 Ethernet, (1) DisplayPort
I/O Ports and connections Head	(4) PC USB 2.0, (1) Optional PC USB 2.0 with 2x20 and/or MSR, (1) 10/100/1000 Ethernet, (1) DisplayPort, USB connections are for customer addable USB dongles
I/O Ports and connections POS Hub	(1) 24 V Powered USB 2.0, (1) 24 V Cash Drawer Port, (4) 12 V Powered USB 2.0

TOSHIBA

Leading Innovation >>>

Specifications

References

✻   MHz/GHz only measures microprocessor internal clock speed; many factors affect applications performance

†   MB/GB equals one million/billion bytes when referring to storage capacity; accessibility may be less

Please Recycle

Premier Business Partner

IBM®

RTL03004-USEN-01