

Coverage	10 m / 33 ft. line of sight
Category	Bluetooth® linear imager scanner
Optical sensor	2500 pixels
Light source	Red LED 625 nm
Resolution	3 mil
Depth of field (depends on barcode resolution)	3.5 to 38 cm / 1.4 to 15 in.
Scanning angle	Pitch $\pm 70^\circ$ , Skew $\pm 70^\circ$
Scan rate	100 scans / second
Barcodes supported	Codabar, Code 39, Code 93, Code 128, GS1 DataBar (RSS), Industrial 2 of 5, Interleave 2 of 5, ISBT-128, Italian and French Pharmacodes, Matrix 2 of 5, MSI, Plessey, Telepen, UPC-A, UPC-E, EAN-8, EAN-13, GS1-128 (EAN-128)
Programmable features	Data editing, interface selection, symbology configuration
Size LxWxH	9.5 x 3.5 x 2 cm / 3.7 x 1.4 x 0.8 in.
Weight (including battery)	1660- 50 g / 1.76 oz. 1661- 69 g / 2.43 oz.
Memory	1660- 256 K 1661- 512K
Temperature	Operating : 0 ° C to 50° C / 32° F to 122° F / Storage : -20° C to 60° C / -4° F to 140° F( w/o battery )
EMC regulation	BSMI, CE, C-tick, FCC, NCC, IC, TELEC, SRMC, KC
Warranty	1 year