

Specifications

SPP-R200

Printing Method	Thermal Line Dot method
Print Speed	Max. 80 mm/sec
Resolution	203 Dpi
Column Capacity	Font A: 32 Columns Font B: 42 Columns
Character Set	Alpha Numeric Character: 95 Extended Graphics: 128 X 20 International Characters: 32
Character Size	Font A: 1.25 x 3 mm (12 x 24 dots) Font B: 0.88 x 3 mm (9 X 24 dots)
Paper Type	Thermal Paper
Paper Size	58 ± 0.5mm, Max. Diameter 40mm
Bar-code type	1D: UPC-A/E, EAN-13/8/18, ITF, Code 39, Code 128, CODABAR, Code 93 2D: PDF417, QR-Code, Maxicode & Data Matrix
Data Buffer	64 Kb
NV Bitmap Memory	256 Kb
Interface	Serial RS-232C USB USB Blue Tooth
Battery	Li-ion, 7.4VDC, Capacity 1200 mAh 500 Cycles rechargeable
Battery Charger	Input: 100~250 VAC, 1.0 A Max. Output: 8.4 VDC, 0.8A
External Dimensions (WxDxH)	79.5 x 126.7 x 43.6 mm
Weight	Printer with Battery 236g
Reliability	Head: 50Km