

Specifications- 1902GHD-2USB-5 / 1902GSR-2USB-5

| | |
|------------------------------------|--|
| Radio/Range | 2.4 to 2.5 GHz (ISM Band) Adaptive Frequency Hopping Bluetooth v2.1; Class 2: 10 m (33') line of sight |
| Battery | 1800 mAh Li-ion minimum |
| Number of Scans | Up to 50,000 scans per charge |
| Expected Hours of Operation | 14 hours |
| Expected Charge Time | 4.5 hours |
| Dimensions (LxWxH) | 104 mm x 71 mm x 160 mm (4.1" x 2.8" x 6.3") |
| Weight | 214 g (7.5 oz) |
| Operating Temperature | 0°C to 50°C (32°F to 122°F) |
| Storage Temperature | -40°C to 70°C (-40°F to 158°F) |
| Light Levels | 0 to 100,000 lux (9,290 foot-candles) |
| Scan Pattern | Area Image (838 x 640 pixel array) (HD): Horizontal: 41.4°; Vertical: 32.2° |
| Scan Angle | (SR): Horizontal: 42.4°; Vertical: 33° (ER): Horizontal: 31.6°; Vertical: 24.4° |
| Print Contrast | 20% minimum reflectance difference |
| Pitch, Skew | 45°, 65° |