

Nexa PX-700II

Thermal Receipt Printer

Overview




The Nexa PX-700II is the successor to the popular PX-700, a high performance thermal printer that is ideal for POS receipt printing and much more.

It's combination of a blisteringly fast 300mm per second maximum print speed, durable and reliable design compatibility with industry standard ESC/POS commands make the PX-700II a winner!

- Triple interface USB, RS232 and Ethernet available
- Compact footprint
- 300mm/sec maximum print speed
- ESC/POS emulation provides compatibility with virtually all POS applications available.
- OPOS compliant



Blisteringly fast
300mm/sec
print speed



Triple interface -
Ethernet + USB
+ Serial

2

year warranty



NEXA

Visit www.nexapos.com to find out about other exciting Nexa products!

Nexa PX-700II


Thermal Receipt Printer

Specifications

Print method	Direct thermal
Print width	64/76mm
Dot density	512/576dot/line
Print speed	300mm/s
Interface	Serial+USB+Ethernet or USB+Parallel
Paper diameter	83mm
Line space	3.75mm(can be adjusted)
Character Size	ANK Font Font A: 12×24dots Font B: 9×17dots Simplified/Traditional Chinese Character: 24×24dots
Code page	PC437/Katakana/PC850/PC860/PC863/PC865/ West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/ PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/ PC737/WPC/1257/Thai Vietnam/PC864/PC1001/(Latvian)/ (PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/ (Thai)
Barcode mode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/ CODABAR/CODE93/CODE128/QRCODE
Fonts	GB18030
Data	128K bytes
NV Flash	256K bytes
Cashdrawer out	DC 24V/1A
Power supply	AC 110V/220V£~50 ~ 60Hz£-DC 24V/2A
Weight	1.23kg
Dimension	180×139×127mm
Operating environment	Temperature:0° ~ 45° Humidity:10% ~ 80%
Storage environment	Temperature:-10° ~ 60° Humidity:10 ~ 90%
Reliability	150km



Blisteringly fast
300mm/sec
print speed



Triple interface -
Ethernet + USB
+ Serial

2

year warranty

NEXA

Visit www.nexapos.com to find out about other exciting Nexa products!